



TECHNICAL DATA

- Hot temp. supply range: 60°C – 85°C
- Adjustable temp. range: 35°C – 60°C
- Max. supply pressure: 10 Bar
- Factory pre-set: 45°C (in the adjustable position)
- Temperature stability: $\pm 3^{\circ}\text{C}$
- Kvs Value: 2.24 m³/h
- Mixing valve inlets: 3/4" FBSP
- Manifold connections: 1" MBSP
- 210mm Centres
- Warranty: 6 Years for Mixing Valve

CONTROL PACK

OVERVIEW

Komfort Komix2 Underfloor Heating Mixing Valve Unit with a choice of 3 UFH pumps; the Grundfos UPM3 FLEX AS, UPM3 Auto and WILO PARA, expertly designed for efficient underfloor heating. Operating at temperatures between 35 to 60°C—tailored to your specific floor construction and building requirements—this pump station features a state-of-the-art KomMix blending valve.



KEY FEATURES

- Temperature range of 35°C – 60°C.
- Equipped with an pressure and temperature gauge in one piece.
- Equipped with an Manual Air Vent.
- 6 Year Warranty On Mixing Valve.

CONTACT US



+44 1600 731555



sales@komfort-ufh.co.uk



Monmouth, NP25 3QG