

**Komfort Loose Cable**



**Technical Data**

- Operating Voltage: 220 – 240v
- Output Rating: 120W, 160W & 240W/m<sup>2</sup>
- IP Rating: IPX7
- Overall Thickness: 4mm
- Inner Insulation: FEP – Outer Insulation: PVC
- Min. Installation Temp: 5°C
- Connection: 2.5m Coldtail
- 25 Year Cable Warranty
- 2m Conduit
- Installation Instructions

Cable Length (m)	Power (W)	120W/m <sup>2</sup>	160W/m <sup>2</sup>	240W/m <sup>2</sup>
		100mm Spacings	75mm Spacings	50mm Spacings
12.5	150	1.25m <sup>2</sup>	0.94m <sup>2</sup>	0.63m <sup>2</sup>
19	225	1.88m <sup>2</sup>	1.41m <sup>2</sup>	0.94m <sup>2</sup>
25	300	2.50m <sup>2</sup>	1.88m <sup>2</sup>	1.25m <sup>2</sup>
31.5	375	3.13m <sup>2</sup>	2.34m <sup>2</sup>	1.56m <sup>2</sup>
37.5	450	3.75m <sup>2</sup>	2.81m <sup>2</sup>	1.88m <sup>2</sup>
44	525	4.38m <sup>2</sup>	3.28m <sup>2</sup>	2.19m <sup>2</sup>
50	600	5.00m <sup>2</sup>	3.75m <sup>2</sup>	2.50m <sup>2</sup>
56.5	675	5.63m <sup>2</sup>	4.22m <sup>2</sup>	2.81m <sup>2</sup>
62.5	750	6.25m <sup>2</sup>	4.69m <sup>2</sup>	3.13m <sup>2</sup>
75	900	7.50m <sup>2</sup>	5.63m <sup>2</sup>	3.75m <sup>2</sup>
87.5	1050	8.75m <sup>2</sup>	6.56m <sup>2</sup>	4.38m <sup>2</sup>
100	1200	10.00m <sup>2</sup>	7.50m <sup>2</sup>	5.00m <sup>2</sup>
112.5	1350	11.25m <sup>2</sup>	8.44m <sup>2</sup>	5.63m <sup>2</sup>
125	1500	12.50m <sup>2</sup>	9.38m <sup>2</sup>	6.25m <sup>2</sup>
150	1800	15.00m <sup>2</sup>	11.25m <sup>2</sup>	7.50m <sup>2</sup>
187.5	2250	18.75m <sup>2</sup>	14.06m <sup>2</sup>	9.38m <sup>2</sup>