



## Komfort Decoupling

### Technical Data

- Operating Voltage: 220 – 240v
- Output Rating: 100W, 135W & 195W/m<sup>2</sup>
- IP Rating: IPX7
- Overall Thickness: 5.5mm
- Inner Insulation: FEP – Outer Insulation: PVC
- Min. Installation Temp: 5°C
- Connection: 2.5m Coldtail
- 25 Year Cable Warranty
- 2m Conduit
- Installation Instructions

Cable Length (m)	Power (W)	100W/m <sup>2</sup>	135W/m <sup>2</sup>	195W/m <sup>2</sup>
		4 notches	3 notches	2 notches
12.5	150	1.50m <sup>2</sup>	1.11m <sup>2</sup>	0.77m <sup>2</sup>
19	225	2.25m <sup>2</sup>	1.67m <sup>2</sup>	1.15m <sup>2</sup>
25	300	3.00m <sup>2</sup>	2.22m <sup>2</sup>	1.54m <sup>2</sup>
31.5	375	3.75m <sup>2</sup>	2.78m <sup>2</sup>	1.92m <sup>2</sup>
37.5	450	4.50m <sup>2</sup>	3.33m <sup>2</sup>	2.31m <sup>2</sup>
44	525	5.25m <sup>2</sup>	3.89m <sup>2</sup>	2.69m <sup>2</sup>
50	600	6.00m <sup>2</sup>	4.44m <sup>2</sup>	3.08m <sup>2</sup>
56.5	675	6.75m <sup>2</sup>	5.00m <sup>2</sup>	3.46m <sup>2</sup>
62.5	750	7.50m <sup>2</sup>	5.56m <sup>2</sup>	3.85m <sup>2</sup>
75	900	9.00m <sup>2</sup>	6.67m <sup>2</sup>	4.62m <sup>2</sup>
87.5	1050	10.50m <sup>2</sup>	7.78m <sup>2</sup>	5.38m <sup>2</sup>
100	1200	12.00m <sup>2</sup>	8.89m <sup>2</sup>	6.15m <sup>2</sup>
112.5	1350	13.50m <sup>2</sup>	10.00m <sup>2</sup>	6.92m <sup>2</sup>
125	1500	15.00m <sup>2</sup>	11.11m <sup>2</sup>	7.69m <sup>2</sup>
150	1800	18.00m <sup>2</sup>	13.33m <sup>2</sup>	9.23m <sup>2</sup>
187.5	2250	22.50m <sup>2</sup>	16.67m <sup>2</sup>	11.54m <sup>2</sup>